



Perma Tech, Inc.

"Your Single Source for ALL Your Loading Dock Needs"

PERMA RAIN DAM

The Perma Tech RAIN DAM keeps moisture out of the loading/unloading area with a remarkable "wiper" pad seal that engages the trailer's top. Protects the dock from moisture infiltration, keeping products safe from costly water damage. It requires virtually no maintenance.

FEATURES & OPTIONS

- ◆ Rain Guard Pad Position: 18 inches in front of the dock seal or shelter providing full height access to trailer opening.
- ◆ Reinforced Foam Pad: 4 inch thick pad reinforced with armour clad belting provides wearability while creating a downward pressure for a consistent seal across entire width of trailer top with standard range.
- ◆ Peaked Head Frame: 1-1/2 x 1-1/2 inch steel tubing frame. Head Frame Cover: 20 ga. galvanized steel, peaked.
- ◆ Optional: Translucent fiberglass, peaked head frame cover
- ◆ Rugged side support brackets for mounting over existing equipment.
- ◆ Metal Mounting Plate: 12 ga. steel. Adds stiffness to the wiper pad.
- ◆ Trailer Height Coverage: From 12 feet 8 inches and higher. Lower truck coverage available with "XL" units.
- ◆ Front seal pad is replaceable



The Perma Rain Dam is available in an "XL" to provide an extended service range for loading docks servicing lower trailers.

SALES & SERVICE BY:



MHI



Perma Tech Inc. | 363 Hamburg Street | Buffalo, New York 14204
P: (800) 362-7325 | F: (716) 854-0774 | www.permatechinc.com